

MATERIAL SAFETY DATA SHEET

Date: March 8, 2009

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: HeatBloc-Ultra
 Item Number: HB-Ultra part B
 Chemical Name: N.A.
 Comparable Products: isn't one
 Company Information: STS Coatings, Inc.
 347 Hwy 289
 Comfort, TX 78013

Emergency Phone: CHEMTREC **800-424-9300**
 General Information: 830-995-5177

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical	CAS No.	TLV	STEL	PEL	CEIL	Weight %
Aluminum	7429-90-5	10 mb/m3	N.E.	15 mg/m3	N.E.	60-64%
Stabilizer	Trade Secret					1-5%

3. HAZARDS IDENTIFICATION

HMIS Rating Health – 1 Flammability – 1 Reactivity – 1 Personal Protection B
 WHMIS Class B3, D2B

POTENTIAL HEALTH EFFECTS:

Likely routes of exposure: Skin contact, inhalation, ingestion

INHALATION: Inhalation of high vapor concentrations may cause irritation in the respiratory tract.

EYE CONTACT: May cause slight irritation.

SKIN CONTACT: Prolonged skin contact may cause irritation.

INGESTION: Irritating to mouth, throat and stomach.

Carcinogenicity

	ACGIH	IARC	NTP	OSHA
Aluminum Powder	N.E.	N.E.	N.E.	N.E.

4. FIRST AID MEASURES

IF IN EYES: Immediately flush with large amounts of potable water for 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Get medical attention.

IF ON SKIN: Remove contaminated clothing and wash skin with soap and water. If irritation persists, seek medical attention. Wash contaminated clothing before reuse.

IF INHALED: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

IF INGESTED: **DO NOT** induce vomiting – aspiration hazard. Give victim plenty of water. Never give anything to an unconscious person. If spontaneous vomiting occurs, be sure to keep victim's head below hips to avoid aspiration of vomit into lungs, monitor for breathing difficulty. Get immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASH POINT: N/A

LOWER EXPLOSIVE LIMIT: N.D.

UPPER EXPLOSIVE LIMIT: N.D.

STS Material Safety Data Sheet

Material: HeatBloc-Ultra

Item No.: HB-U part B

¹ Hazard Ratings: least = 0 slight = 1 moderate = 2 high = 3 extreme = 4 Based upon NPCA guidelines

AUTOIGNITION TEMPERATURE: N.D.
EXTINGUISHING MEDIA: dry chemical foam, water fog
FIRE AND EXPLOSION HAZARDS: Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; CONTAINERS MAY EXPLODE AND CAUSE INJURY OR DEATH. DO NOT PRESSUREIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; CONTAINERS MAY EXPLODE AND CAUSE INJURY OR DEATH. Solid stream of water or foam can cause frothing.
SPECIAL FIREFIGHTING PROCEDURES: At higher temperature pressure build up in sealed containers. Use water to cool containers exposed to fire. As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASE OR SPILLED: Ventilate the area and remove all sources of ignition. Evacuate unnecessary personnel. Take action to eliminate source of leak. Large spills should be handled carefully. Put on respiratory protection and necessary personal protective equipment. Dike or impound spilled liquid. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Repeat absorbent/sweep cycle until the spill has dried up. Avoid runoff into storm sewers and ditches, which lead to waterways. Dispose of container according to local/national regulations.

7. HANDLING AND STORAGE

HANDLING: Use only in area provided with appropriate ventilation. Keep out of reach of children. Take precautionary measures against static discharges. Ground and bound containers when transferring material.
STORAGE: Keep container tightly closed in a dry, cool and well-ventilated place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respiratory protection and respirators when the product is mixed or applied in a poorly ventilated area or if workplace levels of ingredients exceed the TLV. Follow applicable federal, state, and local regulations.

OTHER PROTECTIVE EQUIPMENT: Where contact is likely, wear chemical resistant gloves, chemical safety goggles with a face shield, and clean protective clothing to cover arms and legs to keep exposure to a minimum.

HYGENIC PRACTICES: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. Wash hands before breaks and at the end of workday. Avoid contact with eyes, skin, and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Silver paste	FREEZE POINT:	N.D.
ODOR:	Slight	VAPOR PRESSURE:	N.D.
PH @ 100.0%:	N.D.	VISCOSITY:	N.D.
BOILING RANGE:	212° F	ODOR THRESHOLD:	N.D.
VAPOR DENSITY:	N.D.	SPECIFIC GRAVITY:	1.69
SOLUBILITY IN WATER:	Insoluble		

PARTITION COEFFICIENT (n-octanol/water): N.D.

EVAPORATION RATE: Slower than Butyl Acetate

VOC CONCENTRATION AS APPLIED (less water and exempt solvents): 0 G/L

NOTE: VOC concentration expressed as applied when all components are mixed and applied per manufacturer's instructions.

10. STABILITY AND REACTIVITY

STABILITY: This product is stable under recommended storage conditions.

CONDITIONS TO AVOID: Heat, flames and sparks. Prolonged exposure to high temperatures.

STS Material Safety Data Sheet

Material: HeatBloc-Ultra

Item No.: HB-U part B

¹ Hazard Ratings: least = 0 slight = 1 moderate = 2 high = 3 extreme = 4 Based upon NPCA guidelines

MATERIALS TO AVOID: Alkalis, oxidizing agents, reducing agents, acids.

HAZARDOUS DECOMPOSITION PRODUCTS: Hydrogen

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity

Aluminum Powder LC50 no data available

Acute oral toxicity

Aluminum Powder LC50 no data available

Acute dermal toxicity

Aluminum Powder LC50 no data available

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Generally to hazardous to water.

13. DISPOSAL CONSIDERATIONS

The transportation, storage, treatment and disposal of this waste must be conducted in accordance with all applicable federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT: PROPER SHIPPING NAME: Not regulated

IATA: PROPER SHIPPING NAME: Not regulated

15. REGULATORY INFORMATION

SARA SECTION 313:

This product contains no substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SARA 311-312 (RTK)

This product has been reviewed according to EPA 'Hazard Categories' promulgated under Sections 311 and 312 Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

FIRE HAZARD, IMMEDIATE (ACUTE) HEALTH HAZARD, DELAYED (CHRONIC) HEALTH HAZARD

CERCLA

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

No CERCLA chemicals exist in this product above reportable concentrations.

TSCA Section 12(b) Export Notification

This product contains no chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States.

CA Proposition 65:

Warning: This product contains chemicals known to the State of California to cause cancer, birth defects, and/or other reproductive harm.

There are no Proposition 65 chemicals known to exist in this product.

16. OTHER INFORMATION

STS Material Safety Data Sheet

Material: HeatBloc-Ultra

Item No.: HB-U part B

¹ Hazard Ratings: least = 0 slight = 1 moderate = 2 high = 3 extreme = 4 Based upon NPCA guidelines

Legend:

N.E. – Not Established

TLV – Threshold Limit Value

STEL – Short Term Exposure Limit

PEL – Permissible Exposure Limit

CEIL - Ceiling

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the Manufacturer's knowledge, or is obtained from sources believed by the Manufacturer to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The Manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally the Manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

For Other Product Information Contact:

STS Coatings, Inc.

347 Hwy 289

Comfort, TX 78013

info@stskoatings.com

phone: 830-995-5177

fax: 830-995-5705